

Your Single Source for Valve Automation



BUTTERFLY VALVES





VALVE





GEAR
OPERATORS



FIRE SAFE
FUSIBLE
LINK
ASSEMBLIES

AUTOMATION





anything's possible. just ask.

VALVE AUTOMATION PRODUCT OVERVIEW

AUTOMATED BALL VALVES



STATILLESS STEEL - BRASS PVC/CPVC - Mueri-soar Sammer - Flance Special Service Valves

PNEUMATIC & ELECTRICALLY ACTUATED BALL VALVES Valve styles include 2-piece and 3-piece stainless steel,

brass, 150# ANSI flanged, sanitary clamp end, PVC/CPVC/ polypropylene, and multi-port valves in brass, PVC/CPVC and stainless steel. Most InstruPak automated units are direct actuator mount for low profile, cost-efficient operations.

STAINLESS STEEL 2-PIECE

hitora com/instrupak is series html



SIZE RANGE 1/4" - 3" full port SEATS & SEALS RTFE and TFE PRESSURE RATING 1000WOG/150PSI steam TEMPERATURE RATING 40F to +450F END CONNECTIONS NPT 2-piece design

STAINLESS STEEL 3-PIECE

bitorq.com/instrupak_is_3pt_series.html



SIZE RANGE 1/4" - 3" full port SEATS & SEALS PRESSURE RATING 1000WOG/150PSI steam TEMPERATURE RATING END CONNECTIONS NPT or socket weld 3-piece swing-out design

SANITARY CLAMP END



SIZE RANGE 1/2" - 4" full port SEATS & SEALS Cavity filled TFE PRESSURE RATING 1000WOG/150PSI steam TEMPERATURE RATING END CONNECTIONS sanitary clamp ends

STAINLESS STEEL FLANGED

bitorq.com/instrupak_is_2pf_series.html



SIZE RANGE 1/2" - 4" full port SEATS & SEALS PRESSURE RATING ANSI class 150 TEMPERATURE RATING -40F to +450F min./max END CONNECTIONS designed to ANSI B16.34

STAINLESS 3-WAY NPT





SIZE RANGE 1/2" - 2" full port SEATS & SEALS TFE and RTFE PRESSURE RATING 1000WOG/125PSI steam TEMPERATURE RATING END CONNECTIONS NPT 3-way design (L-port or T-port)

STAINLESS 3-Way FLANGED

bitorq.com/instrupak_is_3wf_series.html



SIZE RANGE 1/2" - 4" full port SEATS & SEALS RTFE and TFE PRESSURE RATING Class 150 TEMPERATURE RATING 40F to +450F **END CONNECTIONS** designed to ANSI B16.34 (L-port or T-port)

BRONZE 2-WAY

bitorq.com/instrupak_iz_series.html



SIZE RANGE 1/2" - 3" full port SEATS & SEALS TFE and BUNA-N PRESSURE RATING 600WOG/125PSI steam
TEMPERATURE RATING -40F to +450F END CONNECTIONS Adjustable Stem Packing

BRONZE 3-WAY

bitorq.com/instrupak_iz_3w_series.html



SIZE RANGE - 2" full port SEATS & SEALS TFE and BUNA-N PRESSURE RATING TEMPERATURE RATING -40F to +450F END CONNECTIONS NPT; 3-way L or T-port Adjustable Stem Packing

BRASS 2-PIECE

bitorq.com/instrupak_ip_series.html



SIZE RANGE 1/4" - 4" full port SEATS & SEALS TFE and Viton®
PRESSURE RATING 600WOG/125PSI steam TEMPERATURE RATING +320F maximum END CONNECTIONS NPT 2-piece design

BRASS 3-WAY

bitorq.com/instrupak_ip_3w_series.html



SIZE RANGE 1/4" - 2" standard port SEATS & SEALS TFE and Viton® PRESSURE RATING 435WOG to 1-1/2 TEMPERATURE RATING END CONNECTIONS NPT 3-way design (L-port or T-port)

PVC/CPVC TRUE UNION

bitorq.com/instrupak_ic_series.html



SIZE RANGE 1/2" - 4" full port SEATS & SEALS TFE, RTFE, BUNA-N or Viton® PRESSURE RATING varies with seal material TEMPERATURE RATING varies with seal material END CONNECTIONS NPT, socket, flanged

PVC/CPVC 3-WAY

bitorq.com/instrupak_ic_3way_series.html



SIZE RANGE 1/2" - 2" SEATS & SEALS TFE, RTFE, BUNA-N, Viton® PRESSURE RATING varies with seal material TEMPERATURE RATING varies with seal material END CONNECTIONS threaded or socket L-port or T-port

AUTOMATED BUTTERFLY VALVES



LUG AND WAFER STYLE
EPOM, BUNA EVIDAL
CAST REST, PVC
POLIFICACINE
METAL BFVS HAVE
STANDARD SS DISCISTAN

PNEUMATIC & ELECTRICALLY ACTUATED BUTTERFLY VALVES Our cast iron lug and wafer style butterfly valves all have stainless steel discs as a standard. EPDM, BUNA-N and Viton® liners are available on all sizes. BI-TORQ® also offers PVC, CPVC, polypropylene, stainless steel and sanitary clamp end butterfly valves for corrosive or sanitary applications.



www.bitorg.com/butterfly valve.html

- CAST IRON BODY WITH STANDARD STAINLESS STEEL DISC
- LUG AND WAFER DESIGN
- STANDARD VALVES 2" THROUGH 12"; ADDITIONAL MODELS AVAILABLE THROUGH 24"
- EPDM, BUNA-N OR VITON® LINERS AVAILABLE
- PNEUMATIC, ELECTRIC OR GEAR OPERATORS

WORKING PRESSURE: WORKING TEMPERATURE:

225PSI TO 8"; 150PSI 10", 12" EPDM: -30F to +275F

BUNA-N: +10F to +180F



- PVC, CPVC AND POLYPROPYLENE VALVE BODIES AND DISCS
- LUG AND WAFER DESIGN
- STANDARD VALVES 2" THROUGH 12"; ADDITIONAL SIZES AVAILABLE UPON REQUEST
- EPDM, BUNA-N OR VITON® LINERS AVAILABLE
- PNEUMATIC, ELECTRIC OR GEAR OPERATORS

WORKING PRESSURE: 150PSI TO 12"
WORKING TEMPERATURE: 73F TO 150PSI

PNEUMATIC ACTUATORS



RACK AND PINION ACTUATORS



SPRING RETURN
DOUBLE ACTING
159/NAMUR MOUNT
RACK & PINION
AMORIZED ALUMINUM
DUAL LIMIT STORS

BI-TORQ offers a full range of pneumatic valve actuators from 40 to 27,000 inch pounds output torque in both double acting and spring return/fail safe design. The star shaped female output shaft and ISO mounting allows for direct mounting a variety of ISO style valves. Our anodized aluminum actuators also offer true ISO and NAMUR accessory mounting for limit switches, solenoids and positioners. All stainless steel or epoxy coated actuators are available for highly corrosive atmospheres. Scotch yoke and linear actuators are also available.

 $www.bitorq.com/pneumatic_actuator_aluminum.html$

STAINLESS STEEL ACTUATORS

CORROSION RESISTANT ACTUATORS
Made from all stainless steel, our SS-PN
pneumatic series offers corrosion resistant
actuation for sanitary, food and chemical
operations. A stream-lined design reduces
the areas where dust and dirt can
accumulate.



Vane Style Actuators





KINETROL VANE STYLE ACTUATORS AND SPRING PACKS

Vane style actuators provide high torque output in relatively small size, making them ideal for applications where supply air pressure is low or space is a concern. Kinetrol's wide range of vane actuators and spring packs are suitable for 1/4 turn valves and dampers. A single moving mechanism ensures long-lasting, consistent performance.

ELECTRIC ACTUATORS







www.bitorq.com/electric_actuator.html

129, 229 AND 24 VAC 12 AND 24 VDC ONFOFF AND MODULATING NEMA 4, 4X AND 7 ACCESSORY OPTIONS

HEAVY DUTY INDUSTRIAL ACTUATORS

Our economic, durable electric actuators feature voltages in 115VAC, 220VAC, 12VDC, 24VDC and 24VAC, with torque outputs to 3800 inch pounds. True ISO bottom mounting allows for direct mounting to ISO valves. A permanently lubricated gear train, integral thermal overload protection and a reversing type motor ensure long-lasting operation and consistent torque output. All BI-TORQ electric actuators have a range of optional accessories, including modulating positioner boards, temperature controls, speed controls, timers, brakes and explosion proof enclosures.

HVAC/DAMPER ACTUATORS

www.bitorq.com/hvac.html

HVAC ACTUATORS FOR DAMPER STYLE VALVES

These actuators are designed for low torque damper and HVAC applications. Economically priced, durable and versatile, this product line is suitable for on-off and spring return operations. Limit switches and other options can be added for a complete automated package. Universal mounting allows AVK Carbo-Bond to retrofit the HVAC series to a wide variety of damper valve styles.



AUTOMATION ACCESSORIES

PNEUMATIC VALVE POSITIONERS



4-20MA on 3-15PSI Phenomic Posmoners NEMA 4X on intensionally safe Pactory Mounted and Tested

www.bitorq.com/positioners.html

PNEUMATIC AND ELECTRO-PNEUMATIC POSITIONERS

Our line of positioners include 3-15PSI pneumatically operated or 4-20mA electro-pneumatic models for a wide variety of control applications. Enclosures are rated for NEMA 4/4X or intrinsically safe with an optional high visibility dome indicator. Other options include integrated limit switches, feedback potentiometers, transmitters and flow control modules. Mounting, piping and testing are done on all complete packages.

NAMUR MOUNT SOLENOID VALVES

BI-TORQ offers a full range of NAMUR mount solenoid valves with voltages in 115VAC, 220VAC, 24VAC, 12VDC and 24VDC with cV factors to 1.8 for high flow applications. These solenoids come with NEMA 4, NEMA 7 or intrinsically safe options. The standard connector is a DIN plug with options for a variety of different coil connections. One unit easily can be converted in the field for 3/2 way (spring return) or 5/2 way (double acting) operations. Dual coils also are available for all NAMUR mount solenoids.

120, 220 AND 24 VAC 12 AND 24 VDC NEMA 4, 4X, 7 OR 9 FIELD CONVERTIBLE 3/2 OR 5/2 WAY DIN CONNECTORS OR FEMALE LEADS

www.bitorq.com/solenoids.htm

NAMUR MOUNT SOLENOIDS



LIMIT SWITCHES



Месьинськ от Реродит г Зитснер NEMA 4, 4X, 7 от 9 Этальнер воме новолог. Аль эмтенер насове 55 важжет Растолу Модитер аль Тертер

www.bitorq.com/switches.htm

ROTARY AND LINEAR LIMIT SWITCHES


BI-TORQ is proud to represent ControLink's line of switches and transmitters, which represent the most innovative technology available in the industry. We offer a full array of switch boxes for quarter-turn actuators in NEMA 4, 4X, 7 and 9 enclosures with intrinsically safe options. The standard switch has 2 SPDT mechanical switches with options for proximity or reed type. All switch boxes for BI-TORQ actuators come standard with a SS mounting bracket. We also offer a superior line of proximity switches for linear and multiturn applications.

SPECIALTY SAFETY DEVICES

FUSIBLE LINK ASSEMBLIES









www.bitorq.com/fusible.htm

FUSIBLE LINK ASSEMBLIES FOR FIRE SAFE VALVES

Our fusible link assemblies are designed for fail safe situations where high temperature heat from a fire results in a main valve springing close when the fusible link breaks. This specially designed system incorporates an API607 fire rated valve, a spring loaded operator, a fusible link and customized mounting assembly. We can supply the assembly on a customer owned valve or mount a complete assembly on our own line of API607 fire safe ball or butterfly valves.

- API607 fire rated ball and butterfly valves
- · heavy duty spring packs and arming devices
- the same valve can be used as BOTH an armed fusible link and a manual valve
- ball valves to 8", butterfly valves to 24"

Spring Return Deadman Safety Handles

Spring return deadman handles help to meet OSHA requirements or plant safety specifications where a valve must return to the closed position automatically after operation. Unlike a standard lever handle or gear operator that will stay in the last position, deadman handles will always return to a pre-designated position. This device can be mounted on a variety of 1/4 turn valve models.

automatically closes the valve when the operator releases the handle

DEADMAN HANDLES

AUTOMATIC CLOSMO SAFETY HANDLE FAIL OPEN OR CLOSED TORQUE OURUTS TO 890 MEN POUNDS CUSTOM MODITAINS





MORE QUALITY VALVE PRODUCTS







www.bitorq.com/manual_valve.html

MANUALLY OPERATED BALL & BUTTERFLY VALVES

BALL, BUTTERFLY, GATE AND SPECIALTY VALVES

Our BÍ-TORQ division offers a full range of manually operated valves in addition to our wide variety of automated packages. Stainless steel, brass and carbon steel valves with a variety of seats/seals can handle a range of applications, including steam service, high pressure and fire safe requirements. Heat extension, deadman and custom made handles are available for most models.

GEAR OPERATORS

Mastergear aluminum gear operators, cast iron gear operators and manual override declutchable gears have been part of our product line for over 15 years. Thanks to our machining capabilities with AVK Carbo-Bond, we can customize drive bushings and bases to fit a variety of valves. We also feature Babbitt chainwheels in addition to standard tubular steel handwheels.

WWW.bitorq.com/gears.htm

CAST Iron, Adminism of 55 Books Customers order submice and modified to fit a watery of waves Decembers Manual Overribes Handwisses, Sauntwisses and T-Bass

GEAR OPERATORS



AUTOMATED

KNIFE GATE

VALVES



SPRING RETURN
DOUBLE ACTING
ISO/NAMUR MOUNT
RACK E PRIION
ANODIZED ALUMINUM
DUAL LIMIT STORS

HEAVY DUTY INDUSTRIAL KNIFE GATE VALVES

Our line of knife gate valves are ideal for tough applications that demand high performance and sure closing. Knife gate valves are suitable for slurries, solids and other thick media such as those found in the pulp and paper industry. We also offer a full array or hydraulic and pneumatic cylinders to create a complete automated package.

www.bitorq.com/knife_gate.html

MOUNTING AND TESTING SERVICES

MOUNTING & TESTING

Mountains & Teorino Senvice



EMERGENCY SERVICE

48-HOUR EMERGENCY SERVICE AND MOUNTING & TESTING

We understand that in a plant shutdown situation, time is of the essence. That is why AVK Carbo-Bond/BI-TORQ offers unique emergency service options to get your line up and running quickly. Most BI-TORQ products can ship on the same day of order, while AVK Carbo-Bond's customized product can ship within 48 hours upon request. We also offer a one week expediting service for your convenience.

In addition, our factory-trained personnel can mount and test complete assemblies for you. This means that we can directly ship a ready to put in line assembly to your customer, saving time and ensuring that the product will function perfectly when it gets to the job site. Whether you require a basic actuator to valve assembly or a complete package with positioners, switches, solenoids and/or gear operators, let us assemble and test the units for you.

For the past two decades, AVK Carbo-Bond has engineered complete bracket, coupler and mounting hardware assemblies to mount any ball, butterfly, plug, gate or damper valve to any make or model of actuator. Our wide range of AutoCad® engineered drawings ensures that we can link virtually any automated valve assembly, whether the valve has been in line for 20 years or needs to be installed by the

end of the week. Carbon steel, stainless steel and epoxy-coated options are available for most mounting kits. We also offer a full range of mounting kits for limit switches and positioners to actuators or

CUSTOMIZED MOUNTING HARDWARE





MOUNTING **H**ARDWARE





Lock-Out DEVICES

THREE-WAY TEE LINKAGES



Custom Broaching

manual valves.





SPECIALTY VALVE EXTENSIONS





1N046 LINLAR DRIVE • P.O. BOX 309 LA FOX, ILLINOIS 60147 USA

> TEL: 630-208-9343 FAX: 630-232-6235 WWW.BITORQ.COM SALES@BITORQ.COM